

WiScope® Image System

WiScope Cystoscope OTU-C380 Series shares the same WiScope Image System with other WiScope Single-Use Digital Flexible Endoscopes

O CYSTOSCOPE SPECIFICATIONS

Model	OTU-C380SR	OTU-C380SL
	OTU-C380RR	OTU-C380RL
Field of View	100°	
Direction of View	Forward	
Depth of Field	2 - 50 mm	
Distal Tip Diameter	9.0 Fr	10.0 Fr
Maximum Outer Diameter of Insertion Portion	15.0 Fr	16.0 Fr
Insertion Tube Outer Diameter	13.8 Fr	15.3 Fr
Working Channel Diameter	6.6 Fr	
Angulation Range	210° Up / 210° Down	
Working Length of Shaft	380 mm	
Package	Blister	Pouch

○ IMAGE SYSTEM SPECIFICATIONS

Voltage	AC 100-240V	
Frequency	50/60Hz	
Key Functions	Brightness Increase	
	Brightness Decrease	
	Zoom	
	Image Freezing	
	White Balance	
Video Output	CVBS/HDMI Output to Monitor	
	USB Output to Computer	
Dimensions	Width 32.5cm x Height 6.5cm x Depth 30.5cm	
Weight	2.7 kg	

OTU

Silicon Valley Based Medical Technology Compan

CONTACT

OTU Medical Inc.

2847A Whipple Rd., Union City, CA 94587, USA

www.otumed.com

sales@otumed.com

+1 (408) 461-9801



WiScope® Single-Use Digital Flexible Endoscope

Cystoscope OTU-C380 Series



Bring smart views to One Time Use (OTU) surgical devices



O MODELS

OTU-C380SR (Slim): Standard Deflection
OTU-C380RR (Slim): Reverse Deflection
OTU-C380SL (Regular): Standard Deflection
OTU-C380RL (Regular): Reverse Deflection




• Bullet-like outline design for easy insertion




- Image resolution of 400×400 pixels
- Multilevel illumination adjustment



- Excellent maneuverability
- Maximal deflection of 210° in two directions
- Self-locking deflection angle



- The ultra-thin insertion tube facilitates operations and minimizes patient injury risks.
- 1:1 implementation of hand movements through to the distal end



 Allows passage of accessory instruments and rapid fluid injection respectively during procedures.